



# Chicago Pneumatic



**CPG 150 JD iT4**

**People. Passion. Performance.**



## Over 100 years of experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, generators, accessories and workshop equipment, please visit [www.cp.com](http://www.cp.com).

## Standard Features

- Reliable John Deere engine and Leroy-Somer alternator
- 33.5 hour run time at 75% load with integrated 219 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 71 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- Remote start connections
- Coolant heater
- External fuel connections

## Options

- Skid-mounted
- Battery charger
- Spare tire
- Tool box
- Rear stabilizer jacks

## Control Panel

A comprehensive instrument panel enables all key operating functions to be supervised without opening the canopy. Analog gauges provide at-a-glance monitoring. Protected by a tough transparent cover, the single panel provides easy start up and control of the generator. The panel also provides full system monitoring to ease operation.

## Technical Data

Model	CPG 150 JD iT4
Rated Prime Power	120 Kw / 150 kVA
Voltage Selections - 1Ø	120/240
Voltage Selections - 3Ø	208/240/480
Amperage Capacity @ 120 volts 1Ø	2 x 400
Amperage Capacity @ 240 volts 1Ø	400
Amperage Capacity @ 208 volts 3Ø	400
Amperage Capacity @ 240 volts 3Ø	361
Amperage Capacity @ 480 volts 3Ø	180
Sound Pressure Level @ 23 feet @ 75% load	71 dB(A)
Fuel Tank Capacity	219 gal.
Fuel Consumption At 75% Load	6.5 gal/hr
Fuel Autonomy At 75% Load	33.5 hr

Engine	John Deere
Model number	6068HFG94
Rated Speed	1800 rpm
Emission Compliance	EPA iT4
Rated Output	172 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	6
Displacement	6.8 L
Engine Control	Electronic

Alternator	Leroy Somer
Model	LSA44.2 S7
Degree Of Protection / Insulation Class	IP23 / H

Convenience Receptacles	
20 amp - 125 volt GFCI duplex	2
50 amp - 125 / 250 volt twist lock	2

Dimensions (LxWxH) & Weight	
Dimensions, mounted on skid	133 x 47 x 78 in.
Weight, wet, mounted on skid	7,484 lbs
Dimensions, mounted on trailer	191 x 94 x 92 in.
Weight, wet, mounted on Trailer	8,541 lbs

**Chicago Pneumatic**  
 Rock Hill Product Company  
 1800 Overview Drive  
 Rock Hill, SC 29730  
[www.cp.com](http://www.cp.com)

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.