



Chicago Pneumatic



People.
Passion.
Performance.

Generators
Full line CPG Series

Technical Data

Full line CPG Series



Model		CPG 25	CPG 45
Rated Prime Power	kW / kVA	20 / 25	36 / 45
Voltage Selections - 1Ø	V	120 / 240	120 / 240
Voltage Selections - 3Ø	V	208 / 240 / 480	208 / 240 / 480
Amperage Capacity @ 120 volts 1Ø	A	2 x 67	2 x 104
Amperage Capacity @ 240 volts 1Ø	A	67	104
Amperage Capacity @ 208 volts 3Ø	A	69	125
Amperage Capacity @ 240 volts 3Ø	A	60	108
Amperage Capacity @ 480 volts 3Ø	A	30	54
Sound Pressure Level @ 23 feet @ 75% load	dB(A)	67	66
Fuel Tank Capacity	US gal.	73	73
Fuel Consumption At 75% Load	US gal. / h	1.4	2.15
Fuel Autonomy At 75% Load	h	45	30

Engine		Isuzu	Isuzu
Model number		4LE2T	4LE2X
Rated Speed	rpm	1800	1800
Emission Compliance		Tier 4 Final	Tier 4 Final
Rated Output at 1800 rpm	HP	31.5	59
Coolant		Water / Glycol	Water / Glycol
Cylinders		4	4
Displacement	L	2.18	2.18
Engine Control		Electronic	Electronic

Alternator		Leroy Somer	Leroy Somer
Model		LSA40M5	LSA42.3S5
Degree Of Protection / Insulation Class		IP23 / H	IP23 / H

Convenience Receptacles			
20 amp - 125 volt GFCI duplex		2	2
50 amp - 125 / 250 volt twist lock		2	2

Dimensions (LxWxH) & Weight			
Dimensions, mounted on skid	Inch	75 x 34 x 54.5	75 x 34 x 54.5
Weight, wet, mounted on skid	Lbs	2,290	2,440
Dimensions, mounted on trailer	Inch	121.5 x 57 x 75.5	121.5 x 57 x 75.5
Weight, wet, mounted on Trailer	Lbs	2,290	2,440



CPG 70	CPG 90	CPG 120	CPG 150
56 / 70	75/94	95 / 120	120 / 150
120 / 240	120 / 240	120 / 240	120 / 240
208 / 240 / 480	208 / 240 / 480	208 / 240 / 480	208 / 240 / 480
2x166	2 x 225	2 x 308	2 x 400
166	225	308	400
194	260	329	400
166	220	285	361
84	112	142	180
67	69	69	71
170	170	170	219
3.2	4.0	5.5	6.5
53	42	30	33.5

John Deere	John Deere	John Deere	John Deere
4045 HFG92	4045 HFG92	4045 HFG93	6068HFG94
1800	1800	1800	1800
EPA Interim Tier 4	EPA Interim Tier 4	EPA Interim Tier 4	EPA Interim Tier 4
96	120	151	172
Water / Glycol	Water / Glycol	Water / Glycol	Water / Glycol
4	4	4	6
4.5	4.5	4.5	6.8
Electronic	Electronic	Electronic	Electronic

Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer
LSA43.2 M45	LSA43.2 L8	LSA44.2 VS45	LSA44.2 S7
IP23 / H	IP23 / H	IP23 / H	IP23 / H

2	2	2	2
2	2	2	2

112 x 44 x 67	112 x 44 x 67	112 x 44 x 67	133 x 47 x 78
5,310	5,310	5,360	7,484
176 x 78 x 80	176 x 78 x 80	176 x 78 x 80	191 x 84 x 92
6,560	6,560	6,610	8,541



Over 100 Years of Experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

Generator Features

- Multi-voltage selector switch
- Remote start / stop
- Environmentally friendly 110% fluid containment frame
- Coolant heater standard CPG 70-150
- Lockable control panel
- Digital control system
- Electronic governing system
- AREP excitation allows for excellent motor starting
- Fluid drains with valves and hoses plumbed to edge of skid

Generator Options

- Skid-mount
- Electric or hydraulic brake trailer
- Battery charger
- Ball coupling
- Spare tire
- Rear stabilizer jacks
- Tool box
- Coolant heater, CPG 25 / 45
- External fuel connections



Chicago Pneumatic offers a full range of construction equipment



The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.

Your dealer:

PMI 2957 042003 July 2015