



GP 5600A

Portable Premium Generators (2500 - 9700 W)



Rugged and powerful premium portable power

Designed for construction, rental and other demanding applications, these quiet, high-performance, portable generators deliver unmatched tool starting and voltage regulation in a rugged compact package. Excellent for powering single or multiple tools on an entire job site or as emergency or standby power. Built with heavy-duty frames and premium components to provide long, trouble-free operation even in abusive environments. Ideal for powering high starting amperage tools such as compressors, grinders, fusion welders as well as all your Wacker Neuson electric power tools.

- Best in class tool starting and voltage regulation due to a unique step-start generator technology with AVR (automatic voltage regulation) and separate excitation winding.
- Central GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures while offering personal protection on all receptacles including 240 Volt. Meets the latest NEC and OSHA jobsite standard
- Unique auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear.
- Full wrap-around frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock-mounting combine to provide outstanding impact protection.
- Honda engine with low oil shutdown. Fully compliant with the latest EPA evaporative emissions regulations.



Technical specifications

Portable Premium Generators

Dimensions

| | |
|------------------------------|---------------------|
| L x W x H Overall | 27 x 21 x 21.2 in |
| L x W x H Shipping | 28 x 21.5 x 23.2 in |
| Weight Dry | 196 lb |
| Operating weight with Fuel | 225 lb |
| Shipping weight without Fuel | 198 lb |

Electrical system

| | |
|-------------------------------------|-------------------------|
| Electrical power Max. Output | 5,600 W |
| Electrical power Continuous Power | 5,000 W |
| Voltage AC - 1 Phase | 120/ 240 V |
| Current AC - 1 Phase | 41.7/ 20.8 A |
| Circuit breaker AC - 1 Phase 2 Pole | 23 A |
| Frequency | 60 Hz |
| Power factor | 1 cos Φ 1~ |
| Receptacles AC Outlet | (2) 125V,20A Duplex |
| Receptacles AC Outlet | 125/ 250V, 30A Twst Loc |
| Receptacles AC Outlet | 125V, 30A Twist Lock |
| Generator model | AVR With Brushes |

Engine / Motor

| | |
|-----------------------------|----------------------|
| Engine / Motor manufacturer | Honda |
| Engine / Motor | GX340 RT2 |
| Fuel type | Gasoline |
| Cylinder | 1 |
| Displacement | 23.7 in ³ |
| Operating performance | 10.7 hp |
| RPM / speed Operating | 3,600 rpm |
| Power Rating Specification | SAE J1349 |
| Fuel consumption | 0.86 US gal/h |
| Tank capacity Fuel | 4.94 US gal |
| Tank capacity Oil | 1.2 US qt |



Runtime

5.8 h

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2014 Wacker Neuson SE.